

SMTInterpol

Version 2.5-19-g0d39cdee

Jochen Hoenicke, Tanja Schindler
University of Freiburg
{hoenicke,schindle}@informatik.uni-freiburg.de

May 25, 2018

Description

SMTInterpol is an SMT solver written in Java and available under LGPL v3. It supports the quantifier-free combination of the theories of uninterpreted functions, linear arithmetic over integers and reals, and arrays. Furthermore it can produce models, proofs, unsatisfiable cores, and interpolants. The solver reads input in SMTLIB format. It includes parsers for DIMACS, AIGER, and SMTLIB version 1.2 and 2.5.

The solver uses variants of standard algorithms for CNF conversion [PG86], congruence closure [NO05], Simplex [DdM06] and branch-and-cut for integer arithmetic [CH15a, DDA09]. The array decision procedure is based on *weak equivalences* [CH15b]. Theory combination is performed based on partial models produced by the theory solvers [dMB08].

The main focus of SMTInterpol is the application track where the incremental usage of the solver is required. This track simulates the typical application of SMTInterpol where a user asks multiple queries. The main focus of the development team of SMTInterpol is the interpolation engine [CH16, HS18]. This makes it useful as a backend for software verification tools. In particular, UltimateAutomatizer, the winner of the SV-COMP 2016 and 2017, uses SMTInterpol.

Competition Version

The version submitted to the SMT-COMP 2018 is a release based on version 2.5 with a few recent bug fixes. This release includes quantifier-free interpolation for the theory of arrays.

Further information about SMTInterpol can be found at

<http://ultimate.informatik.uni-freiburg.de/smtinterpol/>

The sources are available via GitHub

<https://github.com/ultimate-pa/smtinterpol>

Authors

The code was written by Jürgen Christ, Jochen Hoenicke, Alexander Nutz, Pascal Raiola, and Tanja Schindler.

Logics, Tracks and Magic Number

SMTInterpol participates in all tracks: the main track, the application track, and the unsat core track. It supports the logics QF_UF, QF_IDL, QF_RDL, QF_LIA, QF_LRA, QF_LIRA, QF_AX and every combinations of these logics: QF_ALIA, QF_AUFLIA, QF_AUFLIRA, QF_UFIDL, QF_UFLIA, QF_UFLRA.

Magic Number: 716 484 617

References

- [CH15a] Jürgen Christ and Jochen Hoenicke. Cutting the mix. In *CAV*, pages 37–52, 2015.
- [CH15b] Jürgen Christ and Jochen Hoenicke. Weakly equivalent arrays. In *FRODOS*, pages 119–134, 2015.
- [CH16] Jürgen Christ and Jochen Hoenicke. Proof tree preserving tree interpolation. *J. Autom. Reasoning*, 57(1):67–95, 2016.
- [DDA09] Isil Dillig, Thomas Dillig, and Alex Aiken. Cuts from proofs: A complete and practical technique for solving linear inequalities over integers. In *CAV*, pages 233–247, 2009.
- [DdM06] Bruno Dutertre and Leonardo de Moura. A fast linear-arithmetic solver for DPLL(T). In *CAV*, pages 81–94, 2006.
- [dMB08] Leonardo de Moura and Nikolaj Bjørner. Model-based theory combination. *Electr. Notes Theor. Comput. Sci.*, 198(2):37–49, 2008.
- [HS18] Jochen Hoenicke and Tanja Schindler. Efficient interpolation for the theory of arrays. In *IJCAR*, 2018. to appear.
- [NO05] Robert Nieuwenhuis and Albert Oliveras. Proof-producing congruence closure. In *RTA*, pages 453–468. Springer, 2005.
- [PG86] David A. Plaisted and Steven Greenbaum. A structure-preserving clause form translation. *J. Symb. Comput.*, 2(3):293–304, 1986.